

SKUs AVAILABLE

Patented & Pats Pend.







RAM-HOL-GE3FKLU RAM[®] Form-Fit **Locking** Holder for Getac ZX70 - Temp Module Compatible

RAM-HOL-GE3FU

RAM® Form-Fit Non-Locking Holder for Getac ZX70 - Temp Module Compatible





RAM-HOL-GE3NKLU RAM[®] Form-Fit **Locking** Holder for Getac ZX70 - **NFC Reach[™] Compatible**

RAM-HOL-GE3NU

RAM[®] Form-Fit **Non-Locking** Holder for Getac ZX70 - **NFC Reach[™] Compatible**



PRIMARY MARKETS



TRANSPORTATION & LOGISTICS



WAREHOUSE & MANUFACTURING







FEATURES



AVAILABLE IN LOCKING & NON-LOCKING

A set of **two keys are provided** for extra security and peace of mind.



4-HOLE AMPS PATTERN The industry-standard AMPS pattern enables you to mount the device anywhere you need it.



ALL BUTTONS & PORTS FULLY ACCESSIBLE

Maintain full access to the device's buttons and ports while docked.



STYLUS CLIP ATTACHMENT An integrated holder **snaps your**

stylus into place while not in use, complemented by a loophole to tether the stylus to the cradle.



INCLUDES ONE 2-HOLE AMPS ACCESSORY ADD-ON BRACKET

Includes a 2-Hole AMPS add-on bracket for **additional device mounting** such as a phone or scanner.



ATTACH GDS[®] CHARGE[™] ACCESSORY

When connected to a power source, **the attached charger provides power to the device**. When it comes time to upgrade, avoid any rewiring by simply unplugging the power connector and attaching the new charger components.

Compatible with

RAM-GDS-CHARGE-V9U: 20-60VDC Input (ideal for electric forklifts) RAM-GDS-CHARGE-V10U: 10-32VDC Input (ideal for vehicles & propane forklifts)



SPRING-LOADED

The spring-loaded design makes it **easy to insert and remove your tablet**, keeping your device secure in a range of applications.

DISCLAIMERS

3rd Party charging accessories are not compatible with these RAM[®] Holders.

Getac Rotating Hand Strap & Kickstand is compatible with the "Temp Module Compatible" holders but are not compatible with the NFC Reach[™] holders.





1

FEATURES -

	3.86" 9.81cm			
6				6.85" 17.4cm
		•	ſ	
(9.67" 24.56cm		 \rightarrow	

SPECIFICATIONS 6.85" H x 9.67" W x 3.86" D Dimensions 17.4cm H x 24.56cm W x 9.81cm D Input Voltage 12VDC Power Cable 1 Meter Length FCC IC CE Certifications UKCA WEEE RoHS Hardwire Power RAM-GDS-CHARGE-V9U Supply RAM-GDS-CHARGE-V10U



COMPATIBLE MOUNTS -



RAM-101U RAM[®] Double Ball Mount with Two Round Plates - C Size Medium



RAP-401-202U RAM[®] Tough-Claw[™] Large Clamp Double Ball Mount with Round Plate



RAM-101-B-225B2U RAM® Drill-Down Dashboard Mount with Backing Plate - C Size Short



RAM-101U-247-4 RAM[®] 4" Square Post Clamp Mount with Round AMPS Plate - C Size

ACCESSORIES





RAM[®] NFC Reach[™] NFC Extender with Drill-Down Double Ball Mount



RAM-VENT1-RND-50U RAM[®] Vent-Temp[™] with Back Dock Connection for Round Vents



RAM-VENT1-RCT-50U RAM[®] Vent-Temp[™] with Back Dock Connection for Rectangular Vents



RAM[®] TEMP-RIGHT[™] DOCK HEATING MODULE

Contact support@rammount.com for more details